

SPECIFICATION SHEET



Tarkett

THE ULTIMATE
FLOORING EXPERIENCE

Bravado™ Laminate Flooring

April 1 2016

PRODUCT SPECIFICATIONS

HDF-Board	Americore™, No Added Formaldehyde
Thickness:	5/16" (8 mm)
Width:	8 1/16" (20 cm)
Length:	47 5/8" (1.2 m)
Edges:	Beveled
Wear Resistance:	AC3
Planks per Carton:	8
Square Feet per Carton:	21.36 (1.98 m ²)
Weight per Carton (Lbs.):	32 (14.5 kg)
Cartons per Pallet:	60 (slip sheeted at 20/40)
Country of Origin	USA
FloorScore® Certification SCS-EC10.2-2007:	Yes

INSTALLATION

Use:	Residential and Light Commercial
Installation System:	T-Loc Angle-Tap
Location:	Below, on and above grade concrete, above grade plywood and approved existing floors.

- Tarkett laminate flooring must acclimate to the temperature of the room. Place the unopened cartons of laminate lying horizontally in the room in which they will be installed for a minimum of 48 hours before installation.
- Room temperature shall be a minimum of 65°F (18°C). Relative humidity must be between 40% and 70%.
- Substrate must be level to within 1/4" in 8 feet (6.35 mm in 2.4 m).
- Install approved laminate foam underlayment.
- Install a 10mil polyethylene vapor retarder when installing over concrete.
- A minimum 5/16" space is required between flooring and all verticals (walls, cabinets, pipes, etc.).
- Rooms over 40' (12 m) in length or width will require the use of Tarkett T-Molding.
- The long side of each plank is assembled by inserting the long side tongue into the groove side of the previous row at approximately a 30° angle. Gently slide or position the plank so it is approximately 1/4" away from the short side of the previous plank. Rotate plank downward until lying flat.
- Position tapping block squarely along the groove side end joint and gently tap the block to engage the tongue side of the plank into the groove side of the previous plank. To avoid damaging the planks, make sure to tap in the center of the tapping block.
- Do not install cabinets directly on laminate flooring.
- The first and last plank in each row must be at least 12" (30.4 cm) in length.
- Stagger end joints a minimum of 12" (30.4 cm).

CARE AND MAINTENANCE

- Post installation temperature must be maintained between 55° F and 100° F. Relative humidity must be maintained between 40% and 70%.
- Never slide heavy furniture or appliances across the floor. Place plywood on the floor and move the object across the plywood.
- To minimize scratching, equip tables and chairs with proper floor protectors.
- To help prolong the life of the floor, use walk-off mats at outside entrances to collect dirt and debris and excess moisture.
- Sweep or vacuum to remove loose dirt or debris that can scratch the floor.
- Wipe up all spills promptly with a dry cloth.
- When necessary, lightly damp mop floor with Tarkett SureShine Floor Cleaner or equal neutral floor cleaner. Do not use excessive water when cleaning.

WARRANTY

- 25 Year Residential Limited Warranty

See package insert for complete installation and warranty information.



Tarkett

THE ULTIMATE
FLOORING EXPERIENCE